

TankJet® 180

FLUID DRIVEN TANK CLEANER

Directional Unit Provides
Concentrated, High-Impact Cleaning
of Hard-to-Remove Residues


Features and Benefits

- Outperforms other fluid driven tank cleaners – more consistent impact over the entire pressure range
- High-impact cleaning results in shorter cycle times so tanks are returned to service more quickly
- Provides a concentrated cleaning stream that removes difficult residues and heavy sludges from the bottom and shadow areas of the tanks
- Ideal for open top tanks
- Nozzles rotate on multiple axes to create a crisscrossing pattern to thoroughly clean tanks and remove the stickiest of residues
- Food-grade, oil-lubricated or flow-through gearbox designs
- No motors – TankJet 180 tank cleaners are fluid-driven
- Lightweight for easy portability
- Customizable to your operation. TankJet 180 can be used for high-concentration chemical recirculation cleaning or low pressure, high-volume cleaning. All units are built-to-order
- TankJet 180 is designed with built-in strainer to minimize clogging and for long wear life
- Great value – TankJet 180 is competitively priced, provides better performance and comes with the applications expertise and support of the world's leader in spray technology



**TankJet 180
tank cleaner
for tanks up to
80' (24.4 m) in dia.**

Spray Coverage



Ideal for Cleaning:

- Adhesive tanks
- Food processing vats and tanks
- Paint tanks
- Petrochemical/chemical processing reactors
- Processing tanks
- Sludge/wastewater tanks

**Try Before You Buy:
Ask About Our Free 15-Day Trial Program**

Specifications

Max. tank dia.:	80' (24.4 m)
Flow rate range:	30 to 300 gpm (113.5 to 1135.6 l/min)
Pressure range:	40 to 350 psi (2.8 to 24 bar)
Wash cycle time:	10 to 30 min
Max. operating temp.:	250°F (121°C)
Min. tank opening size:	12.25" (31.1 cm)
Inlet connection:	2" NPT (F) with 2-1/2" quick-disconnect (M) 2" NPT (F) with 2-1/2" NST hose thread (M) 2" BSPT (F) with 2-1/2" quick-disconnect (M)
Materials of construction:	Castings – 316 stainless steel Gears – 17-4ph stainless steel O-rings – self-lubricating EPDM or Viton® Seals – high-performance spring-energized PTFE Gear shaft bearing system – PTFE or oilite bearing All other metallurgy – 316 stainless steel
Height:	12.2" (31 cm)
Width including nozzle housing:	12.125" (30.8 cm)
Weight:	29 lbs (13.17 kg)



TankJet 180
tank cleaner

Viton® is a registered trademark of DuPont Performance Elastomers.